

High Clearance Boom Sprayer

Maruyama HI-CLE boom sprayer is built and engineered to work on soft grounds and over irrigated or flooded fields. It is ideal for specialty crops like carrots, lettuce, cabbage, collard greens, spinach, tomatoes, peppers, onions, rice, flowers and many other row crops.

REQUEST DEMO HERE:



SMARTSPRAY

BSA-951CM76S

Tread: 76 inches Tire thickness: 4.7 inches

Equipped with an electronic flow control system SmartSpray, an electronic flow control mechanism that automatically adjusts flow rate and pressure, even when operating at variable speeds



LIGHT WEIGHT

Designed for use on multiple soil conditions especially soft grounds and over-irrigated fields



BSA-951CM

Clearance Height

32 In (81 cm)

Distance between tires

Chemical tank capacity

220 Gallon (850 liter)

Boom length

Telescopic 32 to 52 feet

Boom spray height

Nozzle type

Piston pump

Flow rate

Engine

Engine output

Dry weight

Moving speed

Recommended spray

speed

76 / 80 In (190 / 200 cm)

(9.9 to 15.9 meter)

18 to 52 In (46 to 130 cm)

53 nozzles (2-way)

Maruyama MS1000F

25.3 gpm (100 lpm)

EPA Approved Kubota

D1105 (Diesel)

20.9 hp @ 2600 rpm

3,000 Lbs (1,360 Kg)

0 - 6.89 mph (0 -11 km/h)

2.5 mph (4 km/h)



OUTSTANDING DRIVING PERFORMANCE Slim design and permanent 4X4



BSA-951CM80W

Tread: 80 inches

Tire thickness: 8.2 inches

FORWARD COCKPIT Full 180° view with forward visibility to adjust speed and to verify nozzle performance



MID-TANK LAYOUT

Located in the center of the spray tractor. The weight balance between the front and the back is constant allowing for driving stability even in wet fields



Developed to spray Japanese flooded rice fields, this sprayer has exceptional traction and performance on soft soils.



FOR MORE INFORMATION OR TO REQUEST A DEMO CONTACT US MARUYAMA U.S., INC.

Email:maruyama@maruyama-us.com Phone: (972) 940-7400